



P-YI-220 Homopolymer

Description:

"Polynar P-YI-220" is a high melt flow homo-polymer polypropylene for the production of CF, BCF and fine denier staple fibers at medium to high spinning speeds and exhibits excellent antigasfading properties.

"Polynar P-YI-220" offers a high homogeneity, stable extrusion and excellent processability on both short and long spinning lines. This grade allows a high stretch ratio and gives tough and resilient fibers.

Another typical application is high tenacity continuous filament for straps for backpacks, sport bags, bulk bags and handles for big and safety belts. Continuous filament with medium tenacity is used for upholstery and sportswear and heavy duty clothing.

"Polynar P-YI-220" is also suited for the production of bulked continuous filament for thermo bonding and carpets.

"Polynar P-YI-220" is suitable for food contact.

Processing Method:

Fiber Extrusion (CF, BCF, staple)

Features:

High melt flow
Excellent antigasfading properties
Good processability
Homopolymer

Typical Applications:

Wipes and tissues
Straps for backpacks, sport bags, bulk bags and for safety belts
Upholstery and sportswear
Bulk continuous filament for carpets

TYPICAL PROPERTIES	VALUE	UNIT	METHOD
Physical			
Melt Flow Rate (230 °C, 2.16kg)	22.0	g/10min	ASTM D1238
Density	0.90	g/cm ³	ASTM D1505
Mechanical			
Flexural Modulus	1650	MPa	ASTM D790
Tensile Strength at Yield	35	MPa	ASTM D638
Tensile Elongation at Yield	12	%	ASTM D638
Izod Impact Strength (notched) at 23 °C	30	J/m	ASTM D256
Thermal			
Vicat softening point (10N)	154	°C	ASTM D1525
H.D.T. (0.46 Mpa)	95	°C	ASTM D648

Head Office: NO:10 ,Danially Alley ,Andarzgoo Boulevard, TEHRAN-IRAN
 TEL:(+9821)22212087 FAX:(+9821)22201946

Factory: West of TABRIZ Petrochemical Complex – TABRIZ-IRAN
 TEL:(+98411)4201000 FAX:(+98411)4201001
 www.polynar.com Email:info@polynar.ir

